

ET5-S Standard Ruffneck™ Thermostat

Heavy Duty Line Voltage Thermostat

- Temperature range: 40°F to 80°F (5°C to 25°C)
 - 22 amps, 277 VAC
 - ¾ HP @ 125 VAC
 - 1½ HP @ 250/277 VAC
 - Single pole
 - Single Throw*
 - Approximate Shipping Weight: 0.6 lbs (0.28 kg)



XTWA Explosion-Proof Thermostat




- Temperature range: 0°F to 100°F (-18°C to 40°C)
- Class I, Division 1 & 2 Groups A, B, C & D
Class II, Division 1 & 2 Groups E, F & G
Class III, Division 1 & 2
- Sensing bulb in Fined Thermowell for Air Sensing
- 15 amps Res., 600 VAC Max. - 25 amps Res., 277 Max.
- XTWA04481 (Single Pole, Single Throw)*
- XTWA04483 (Double Pole, Single Throw)*
- Approximate Shipping Weight: 4.0 lbs (1.8 kg)

TF115 NEMA 4X Corrosion Resistant Thermostat

- Temperature range: 40°F to 90°F (4°C to 30°C)
- 25 amps Res., 480 VAC Max.
- Full load = 16 amps @ 120 VAC
12 amps @ 240 VAC
Lock Rotor = 80 amps @ 120 VAC
60 amps @ 240 VAC
- single pole, double throw (heating or cooling applications)
- Approximate Shipping Weight: 0.69 lbs (0.31 kg)



XTD8-S Explosion-Proof Thermostat



- Temperature range: 40°F to 80°F (5°C to 25°C)
- Class I, Division 1 & 2 Groups C & D
Class II, Division 1 & 2 Groups E, F & G
Class III, Division 1 & 2
- Feed-thru model (includes explosion-proof plug)
- ¾" - 14 NPT conduit opening (½" conduit adapter included)
- single pole, double throw (heating or cooling applications)
- 22 amps, 277 VAC Max.
- ¾ HP @ 125 VAC
- 1½ HP @ 250/277 VAC
- Approximate Shipping Weight: 5.3 lbs (2.4 kg)

XTB Explosion-Proof Thermostat

- Temperature range: 0°F to 100°F (-18°C to 40°C)
- Class I, Division 1 & 2 Groups C & D
Class II, Division 1 & 2 Groups E, F & G
Class III, Division 1 & 2
- Remote sensing bulb with 57" capillary length
- 15 amps Res., 600 VAC Max. - 25 amps Res., 277 Max.
- XTB04481 (Single Pole, Single Throw)*
- XTB04483 (Double Pole, Single Throw)*
- Approximate Shipping Weight: 3.8 lbs (1.7 kg)



Note:

All 3 phase motors on AH, HP and FR heaters require a motor starter (supplied by others).

*Heating applications only

ET5-S, XTB, XTWA, XTD8-S